TECHNICAL REPORT TO THE PRAIRIE PROVINCES WATER BOARD COMMITTEE ON HYDROLOGY

RETURN FLOW FROM IRRIGATION

SOUTHERN ALBERTA

PPWB REPORT #72, OCTOBER 1985

ENVIRONMENT CANADA
INLAND WATERS DIRECTORATE
WATER RESOURCES BRANCH
HYDROLOGY DIVISION
CALGARY, ALBERTA

The present report is an update to the technical report to the Prairie Provinces Water Board (PPWB) Committee on Hydrology entitled "Natural Flow - Determination of Irrigation Return Flow in Southern Alberta", Environment Canada, March 1974, and deals specifically with the estimation of return flow from the Lethbridge Northern, St. Mary River, Taber, Magrath, Raymond, Mountain View, Leavitt, Aetna and United irrigation districts in the Oldman River Basin. These are the irrigation districts studied in the aforementioned report and to date no study has been undertaken to evaluate the current procedure of estimating return flows from diversions in the Bow River Basin.

An evaluation of the existing relationships for return flow estimation revealed the need for revisions. Subsequent to the analysis of all available data, new return flow regression equations are recommended for the Lethbridge Northern, St. Mary River, and Taber irrigation districts. These new equations require the use of eleven index stations, as compared to nine for the 1974 equations; however, by using existing stations and relocating others, the recommendations result in no net increase in the number of hydrometric stations.

A new relationship is recommended for return flow estimation from the Magrath and Raymond irrigation districts and revised "percentage-of-diversion" estimates are recommended for the Mountain View, Leavitt, Aetna, and United irrigation districts.

TABLE OF CONTENTS

		Page
	SYNOPSIS	i
1.	INTRODUCTION	1
2.	SUMMARY AND RECOMMENDATIONS	3
	2.1 Lethbridge Northern Irrigation District 2.2 St. Mary River and Taber Irrigation Districts 2.3 Magrath and Raymond Irrigation Districts 2.4 Mountain View, Leavitt and Aetna Irrigation Districts 2.5 United Irrigation District 2.6 Future Reliability of the Recommended Return Flow Estimations	3 4 5 5 5 6
3.	EVALUATION OF PRESENT RETURN FLOW ESTIMATION	7
4.	RETURN FLOW MONITORING PROGRAM	11
5.	DATA ANALYSIS	15
	5.1 Lethbridge Northern Irrigation District	15
	Taber Irrigation District	23
	5.3 Magrath Irrigation District and Raymond Irrigation District	35
	5.4 Mountain View, Leavitt and Aetna Irrigation Districts	35
	5.5 United Irrigation District	37
6.	BIBLIOGRAPHY	41
	APPENDIX - Return Flow Data	43

	·	
	-	

FIGURES

			Page
Figure	1:	Trends in Irrigated Land, Consumptive Use and Return Flow - S.M.R.I.D., T.I.D., M.I.D., R.I.D.	9
Figure	2:	Trends in Irrigated Land, Consumptive Use and Return Flow - L.N.I.D.	10

PLATES

		Page
PLATE 1:	Alberta Agriculture, Irrigation Division - Irrigation Districts, March 1974	13
PLATE 2:	Alberta Agriculture, Irrigation Division - Lethbridge Northern Irrigation District	55
PLATE 3:	Alberta Agriculture, Irrigation Division - St. Mary River Irrigation District - West	65
PLATE 4:	Alberta Agriculture, Irrigation Division - Taber Irrigation District	67
PLATE 5:	Alberta Agriculture, Irrigation Division - St. Mary River Irrigation District - Central	69
PLATE 6:	Alberta Agriculture, Irrigation Division - St. Mary River Irrigation District - East	71
PLATE 7:	Alberta Agriculture, Irrigation Division - Magrath and Raymond Irrigation Districts	75
PLATE 8:	Alberta Agriculture, Irrigation Division - Mountain View, Leavitt, Aetna and United Irrigation Districts	79

TABLES

		Page
Table 1	Selected Independent Variables Lethbridge Northern Irrigation District	16
Table 2	Dependent Variable - Total Return Flow for Data Sets in Table 1 - Lethbridge Northern Irrigation District	17
Table 3	Regression Analysis - Lethbridge Northern Irrigation District	18
Table 4	Comparison Between Recommended and Previous (1974) Return Flow Equations - Lethbridge Northern Irrigation District	22
Table 5	Selected Independent Variables - St. Mary River Irrigation District and Taber Irrigation District	24,25
Table 6	Combined Total Return Flow - St. Mary River Irrigation District and Taber Irrigation District	26
Table 7	Dependent Variable - Total Return Flow for Data Sets in Table 6 - St. Mary River Irrigation District and Taber Irrigation District	27
Table 8	: Regression Analysis - St. Mary River Irrigation District and Taber Irrigation District	28
Table 9	: Comparison Between Recommended and Previous (1974) Return Flow Equations - St. Mary River Irrigation District and Taber Irrigation District	34
Table 1	0: Calculation of Return Flow as a Percentage of Diversion - Mountain View Irrigation District	36
Table 1	1: Calculation of Return Flow as a Percentage of Diversion - United Irrigation District	38

TABLES (cont'd)

		Page
Table 71-1:	L.N.I.D 1971 Return Flow Data	45
Table 72-1:	L.N.I.D 1972 Return Flow Data	46
Table 79-1:	L.N.I.D 1979 Return Flow Data	47
Table 81-1:	L.N.I.D 1981 Return Flow Data	51
Table 71-2:	S.M.R.I.D 1971 Return Flow Data	57
Table 72-2:	S.M.R.I.D 1972 Return Flow Data	58
Table 79-2:	S.M.R.I.D 1979 Return Flow Data	59
Table 81-2:	S.M.R.I.D 1981 Return Flow Data	60
Table 71-3:	T.I.D 1971 Return Flow Data	61
Table 72-3:	T.I.D 1972 Return flow Data	62
Table 79-3:	T.I.D 1979 Return Flow Data	63
Table 81-3:	T.I.D 1981 Return Flow Data	64
Table 79-4:	M.I.D 1979 Return Flow Data	73
Table 81-4:	M.I.D 1981 Return Flow Data	73
Table 72-5:	R.I.D 1972 Return Flow Data	74
Table 79-5:	R.I.D 1979 Return Flow Data	74
Table 81-5:	R.I.D 1981 Return Flow Data	74
Table 72-6:	M.V.I.D 1972 Return Flow Data	77
Table 79-6:	M.V.I.D 1979 Return Flow Data	77
Table 81-6:	M.V.I.D 1981 Return Flow Data	77
Table 79-7:	U.I.D 1979 Return Flow Data	
Table 81-7:	U.I.D 1981 Return Flow Data	78

1. INTRODUCTION

The present report is an update to the technical report to the Prairie Provinces Water Board (PPWB) Committee on Hydrology entitled "Natural Flow - Determination of Irrigation Return Flow in Southern Alberta", Environment Canada, March 1974, and deals specifically with the estimation of return flow from the Lethbridge Northern, St. Mary River, Taber, Magrath, Raymond, Mountain View, Leavitt, Aetna and United irrigation districts.

The PPWB accepted the methodology and hydrometric network proposed in the report "Natural Flow - South Saskatchewan River below Red Deer River", Environment Canada, September 1974, and recognized that, as irrigation systems and methods evolve, it would likely be necessary to modify the return flow monitoring network. At that time, it was considered advisable to review the return flow estimation procedures and monitoring network at approximate 10-year intervals. Chapter 3 of the present report provides an evaluation of the existing return flow estimation.

Due primarily to a perceived change in return flow volumes and patterns resulting from the increasing trend toward the use of mechanical sprinkler systems beginning about the mid-1970's, the PPWB recommended a field program to verify the return flow estimates and the monitoring network. Consequently, a field program was conducted during the 1979 and 1981 irrigation seasons to collect return flow data from 173 sites in the study area. Chapter 4 includes a map (PLATE 1) of the study area. PLATES 2 through 8 (in Appendix) show the irrigation districts in detail with the location of all significant return flow sites and recommended index stations. The data collected during 1979 and 1981 was combined with data collected during the original study in 1971 and 1972, and placed in the Appendix to this report.

Chapter 5 presents a detailed data analysis and rationale for the recommended relationships to estimate return flow from each irrigation district. Chapter 2 summarizes the results and recommendations of the study.

2. SUMMARY AND RECOMMENDATIONS

The results of the evaluation of present return flow estimation carried out in Chapter 3 show a definite need to revise existing return flow relationships. That need was brought about by a significant, though gradual change in irrigation practice; primarily a changeover to mechanical sprinkler systems during the mid-1970's in the Lethbridge Northern (L.N.I.D.), St. Mary River (S.M.R.I.D.), and Taber (T.I.D.) irrigation districts.

The field program conducted in 1979 and 1981 collected data from 173 return flow sites and, together with the data collected in 1971 and 1972, formed the basis for the analyses described in Chapter 5. The following sections summarize the present recommendations for the determination of total return flow from the irrigation districts under study.

2.1 Lethbridge Northern Irrigation District

On a monthly basis,

(L.N.I.D.) Return Flow $(dam^3) = 338.34 +$

 $0.955X_1 + 1.308X_2 + 1.237X_3 - 1.251X_4 + 0.830X_5$

using monthly recorded flows (dam3) at the following index stations:

X₁ = Piyami Drain near Picture Butte (05AD037)

 X_2 = Battersea Drain near the Mouth (05AD038)

 X_q = Little Bow River near the Mouth (05AC023)

 X_h = Little Bow River below Travers Dam (05AC012)

 X_5 = Drain L-5 near Diamond City

The recommendation would involve a net increase of one hydrometric station (Drain L-5 near Diamond City), since all others are presently in existence. Table 4 (page 22) shows the improvement in return flow estimation when the recommended equation is applied.

2.2 St. Mary River and Taber Irrigation Districts
On a monthly basis.

(S.M.R.I.D. + T.I.D.) Return Flow $(dam^3) = 1554.1 +$

 $1.558X_1 + 2.132X_2 + 2.106X_3 + 3.631X_4 + 3.064X_5 +$

1.322X₆

using monthly recorded flows (dam3) at the following index stations:

 X_{η} = Seven Persons Creek at Medicine Hat (05AH005)

 X_2 = Drain S-10 near Bow Island (05AJ003)

 X_q = Drain S-4 near Grassy Lake (05AJ002)

 $X_n = T-1$

 X_g = Bountiful Coulee Inflow near Cranford (05AG026)

 $X_6 = II$

NOTE: The index stations shown here are identical to those shown in Chapter 5; only the X_i numbers were changed here for convenience.

Four of the recommended index stations are presently in existence and, while use of the recommended equation would require the establishment of two new recording stations (i.e., T-1, and II), it is likely that three of the present index stations (i.e., Bountiful Coulee near Cranford - 05AG008, Drain T-2 near Taber - 05AG023 and Drain T-11 near Fincastle - 05AG025) would be discontinued. There would, therefore, be a net decrease of one hydrometric station. Table 9 (page 34) shows the significant improvement in return flow estimation when the recommended equation is applied.

2.3 Magrath and Raymond Irrigation Districts

On a monthly basis,

(M.I.D. + R.I.D.) Return Flow (dam^3) = Monthly Recorded Flows (dam^3) at Dry Coulee near Magrath (05AE041) + Pothole Creek at Russell's Ranch (05AE016).

As evidenced by field inspections and the data collected, more than 95% of the return flow from the M.I.D. and R.I.D. is accounted for by those two recording stations.

2.4 Mountain View, Leavitt, and Aetna Irrigation Districts

Based on the considerations explained in Section 5.4, it is recommended that Mountain View, Leavitt and Aetna irrigation districts' monthly return flow be determined as a percentage of the respective monthly diversion recorded by the gauge on the Mountain View Irrigation District Canal (05ADO17), as follows:

May	<u>June</u>	<u>July</u>	Aug.	<u>Sept.</u>	Oct.
100%	100%	40%	35%	20%	35%

2.5 United Irrigation District

Based on the considerations explained in Section 5.5, it is recommended that United Irrigation District monthly return flow be determined as a percentage of the respective monthly diversion recorded by the gauge on the United Irrigation District Canal near Hill Spring (05AD013), as follows:

<u>May</u> <u>June</u>		<u>July</u>	Aug.	<u>Sept.</u>	Oct.
100%	100%	35%	30%	25 %	20%

2.6 Future Reliability of the Recommended Return Flow Estimations

Most irrigation districts under present consideration are undergoing a continual process of upgrading. As distribution systems are made more efficient (e.g., lined vs unlined canals and sprinkler vs gravity-feed irrigation) it is expected that the recommended return flow relationships will become less accurate each year subsequent to 1981. An ongoing contact with irrigators and district managers is therefore recommended to keep abreast of changes. Further, it is recommended that a full return flow monitoring program be carried out in the field every five to ten years.

3. EVALUATION OF PRESENT RETURN FLOW ESTIMATION

The 1974 report (6.1) recommended a procedure to check the reliability of the established regression equations in subsequent years. In an attempt to follow that procedure, precipitation data for Lethbridge, Vauxhall, and Medicine Hat was compiled for the years 1972 to 1981 inclusive, and seasonal moisture conditions (i.e., wet, normal or dry) for those years were identified for the S.M.R.I.D and L.N.I.D. (according to Table 10 from the 1974 report). Tables 8 and 9 from the 1974 report give return flows as a percentage of the respective diversions to the S.M.R.I.D and L.N.I.D. The 1974 report suggests that if, in years subsequent to 1972, the return flows computed from the regression equations differ significantly from those table values, then it is likely that a change in irrigation practice has occurred. While there were significant differences for all years subsequent to 1972, it is not certain whether those differences reflect a change in irrigation practice or whether the derivation of Tables 8, 9 and 10 in the 1974 report was in error.

Further to the previous considerations, there was a perceived change in return flow volumes and patterns occurring about the mid-1970's. Consequently, a field program was conducted during the 1979 and 1981 irrigation seasons to again monitor the return flows. In addition, a field inspection was carried out in 1982, together with some twenty individual interviews with managers and irrigators in the S.M.R.I.D. and L.N.I.D., to determine the extent of and dates of changeover to sprinkler irrigation.

It was determined that significant, though not abrupt, changeover to sprinkler systems began about 1976 in the S.M.R.I.D. and somewhat earlier in the L.N.I.D.

Figures 1 and 2, showing irrigated land, unit consumptive use and unit return flow together with the indicated trends, were plotted for the St. Mary River, Taber, Magrath, and Raymond irrigation districts (Fig. 1) and the L.N.I.D. (Fig. 2). As shown in both figures, there was a decreasing trend in consumptive use and return flow with increasing irrigated land, thereby indicating a more efficient use of irrigation water. These trends and the significant changeover to sprinkler irrigation dictate the need to revise the existing return flow estimations.

FIGURE |

TRENDS IN IRRIGATED LAND, CONSUMPTIVE USE AND RETURN FLOW





FIGURE 2

TRENDS IN IRRIGATED LAND, CONSUMPTIVE USE AND RETURN FLOW




-10-

4. RETURN FLOW MONITORING PROGRAM

The field program carried out during the 1979 and 1981 irrigation seasons collected data from 173 return flow sites. Plate 1 shows the extent and location of all irrigation districts in Alberta and Plates 2 through 8 (in Appendix) are enlargements of the individual irrigation districts under present study, and show the existing distribution systems and locations of significant return flow channels. The data collected during 1971, 1972, 1979, and 1981 have been placed in the Appendix.

-12-

•





-			

5. DATA ANALYSIS

5.1 Lethbridge Northern Irrigation District (L.N.I.D.)

The return flow data collected from the L.N.I.D. for the years 1971, 1972, 1979 and 1981 are included in the Appendix as Tables 71-1, 72-1, 79-1, and 81-1. The data was screened for sites having significant flow volumes for most of the four years being considered. The return flows selected as independent variables for the subsequent regression analysis are shown in Table 1. The volumes shown in Table 1 were derived by first assuming each spot-measurement value from Tables 71-1, 72-1, 79-1, and 81-1 as representing a daily mean flow and using that value to generate a monthly flow volume (i.e., according to the particular month during which the spot measurement occurred). In the same manner, the total measured return flows shown in Tables 71-1, 72-1, 79-1, and 81-1 for each period were used to generate the total return flow volumes shown in Table 2, and were used as the dependent variables in the regression analysis. Thus, 24 data sets were derived for the L.N.I.D. analysis.

TABLE 1

SELECTED INDEPENDENT VARIABLES

LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.)

(All Figures in dam³)

Data sets derived for the years shown		1971				1972							
Selected Indep. Variables (Return Flow Stations)	1	2	3	4	5	6	1	2	3	4	5	6	7
L-6: Piyami Drain (05AD037)	1042	1623	2480	1424	1403	1396	903	1974	2359	1517	1593	1196	1214
L-13: Battersea Drain (05ADO38)	623	2162	1122	1130	2356	1138	887	1028	1744	1631	1198	1541	713
Little Bow River at the Mouth (05AC023)	4464	5937	6162	5551	5397	3787	7289	6136	4809	6090	4680	3472	3466
Little Bow River below Travers Dam (OSACO12)	2205	1554	1716	1500	1343	1453	3451	2429	2124	842	789	763	736
L-1 -	235	40	235	235	477	341	228	308	36	190	387	1	114
L-4	0	19	0	0	0	0	0	0	0	30	0	0	0
L-5	433	57	986	910	827	228	1176	1651	751	106	940	1549	523
L-7	152	547	475	147	903	827	432	35 <i>2</i>	425	493	114	609	940
L-9	330	410	58	95	21	326	22	1	83	265	144	381	8
С	7	0	12,1	4	1	2	64	9	9	7	-	18	7
D	81	0	11	42	62	121	114	12	14	65	129	117	74
I	176	0	23	95	117	349	28	22	74	99	-	24	24

Data sets derived for the years shown Selected	1979							1981						
Indep. Variables (Return Flow Stations)	1	2	3	4	5	6	1	2	3	4	5			
L-6: Piyami Drain (05AD037)	1251	1127	733	1327	623	746	1150	1875	1365	1684	1389			
L-13: Battersea Orain (05ADO38)	1152	620	588	1342	1232	1482	658	1490	1589	1379	1602			
Little Bow River at the Mouth (05AC023)	3235	1936	1550	3798	2820	2921	4396	6332	7323	5526	4759			
Little Bow River below Travers Dam (05AC012)	998	1309	1457	1267	1033	918	2773	2758	2792	2820	2670			
L-1	62	0	64	356	70	351	0	-	201	129	103			
L-4	36	27	0	421	52	423	0	179	1157	472	223			
L-5	308	276	3	316	23	75	0	153	228	251	197			
L-7	270	78	5	37	10	75	21	56	182	176	101			
L-9	122	145	3	75	31	5	65	244	212	104	-			
С	187	99	13	8	3	11	23	161	13	41	8			
D	18	16	19	37	8	56	44	134	78	18	67			
1	187	35	3	0	10	62	0	21	3	0	190			

TABLE 2

DEPENDENT VARIABLE

TOTAL RETURN FLOW FOR DATA SETS IN TABLE 1

LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.)

(All Figures in dam³)

Data sets derived for the years shown	1971						1972						
Dependent Variable	1	2	3	4	5	6	1	2	3	4	5	6	7
Total Return Flow	5537	9567	10248	8326	10516	7457	7867	9422	8595	9940	9037	8357	6661

Data sets derived for the years shown		1979	· · · · · · · · · · · · · · · · · · ·	1981							
Dependent Variable	1	2	3	4	5	- 6	1	2	3	4	5
Total Return Flow	7237	3945	1470	7283	3865	5742	3940	9107	9894	7141	6426

TABLE 3 REGRESSION ANALYSIS LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.)

	CO	TRIAI MBINAT		-	REGRESSION EQUATIONS	MULTIPLE CORRELATION COEFFICIENT	STANDARD ERROR OF ESTIMATE (%)	DATA SETS USED IN ANALYSIS	INDEX STATIONS REQUIRED
	1971 1971	1972 1972	1979 1979	1981 1981	Y=1540.03+1.477X ₁ +1.436X ₉ -1.656X ₄ Y=1328.62+1.693X ₁ +1.160X ₃ -1.311X ₄ +1.471X ₈	.95 .91	10.5 15.2	24 24	3 4
	1971	- (1979	1981	Y=2048.26+1.875X3-2.065X4+5.597X7	.96	11.8	17	3
	-	1972 1972 1972	1979 1979 1979	1981 1981 1981	Y=455.60+1.270X ₁ +1.130X ₂ +1.219X ₁ -1.332X ₄ +0.788X ₅ Y=1203.04+1.732X ₁ +1.239X ₁ -1.544X ₄ +0.915X ₅ +1.412X ₈ Y=1056.22+1.643X ₁ +1.245X ₁ -1.624X ₄ +1.082X ₅ +6.591X ₇ +1.700X ₈	.98 .98 .99	8.3 8.2 5.9	18 18 18	5 5 6
	1971	1972	- '	1981	No Significant Equation				
	1971	1972	1979	-	Y=1676.25+1.495X1+1.370X3-1.567X4	. 95	11.2	19	3
*	- -	1972 1972 1972	- -	1981 1981 1981	Y=1389.69+1.576X ₁ +1.373X ₈ -1.497X ₉ Y=918.24+1.538X ₁ +1.359X ₃ -1.408X ₄ +0.667X ₅ Y=338.34+0.955X ₁ +1.308X ₂ +1.237X ₈ -1.251X ₉ +0.830X ₅	.93 .96 .98	9.3 8.1 5.5	12 12 12	3 4 5
	1971	-	-	1981	No Significant Equation			11	
	1971	-	1979	-	No Significant Equation			12	
1	-	1972	1979	-	Y=1227.03+1.795X1+1.347X1-1.475X4	.96	11.6	13	3
	- - -	-	1979 1979 1979 1979	1981 1981 1981 1981	Y=1285.19+1.703Xs-1.686Xs+6.031Xs Y=662.60+2.779Xs+1.682Xs-2.554Xs Y=784.92+1.780Xs+1.649Xs-2.172Xs+2.962Xs Y=1336.04+1.449Xs-1.589Xs+7.012Xs+14.072Xs	.98 .99 .99	8.8 7.9 7.3 5.4	11 11 11	3 3 4 4
	-	-	1979	-	Y=2821.70+3.954X ₁ +1.185X ₂ -4.244X ₄	. 99	8.5	6	3

^{*} Recommended Equation

 X_1 = L-6 Piyami Drain (05AD037) X_2 = L-13 Battersea Drain (05AD038) X_3 = Little Bow River near the Mouth (05AC023) X_4 = Little Bow River below Travers Dam (05AC012) X_5 = L-5 X_6 = L-7 X_7 = C X_8 = L-4

Table 3 shows the trial combinations of data sets used in the regression analysis. The computer program MULCOR (6.2) was first applied and the resulting regression equations were verified using the P9R (6.3) program. The recommended equation

(L.N.I.D.) Monthly Return Flow (dam³) = 338.34 + $0.955X_1$

 $+ 1.308X_2 + 1.237X_3 - 1.251X_4 + 0.830X_5$

using monthly recorded flows (dam³) at the following index stations:

 X_{γ} = Piyami Drain near Picture Butte (05AD037)

 X_2 = Battersea Drain near the Mouth (05AD038)

 X_{q} = Little Bow River near the Mouth (05AC023)

 X_{4} = Little Bow River below Travers Dam (05AC012)

 X_6 = Drain L-5 near Diamond City

was chosen from Table 3 based on the following considerations:

(a) Statistical Significance

Multiple Correlation Coefficient = 0.98

Coefficient of Determination = 0.96

Standard Error of Estimate = 5.5%

Student's "t"-test was applied to the regression coefficients of the recommended equation and the computed "t-values" were tested at the 95% confidence level.

<u>Independent Variable</u>	Regression Coefficient	"t"
x_1	.955	2.53
x ₂	1.308	3.06
x ₃	1.237	9.12
x ₄	-1.251	-6.97
X ₅	.830	3.47

The minimum acceptable "t-value", at the 95% confidence level, is 2 and is exceeded for each of the regression coefficients.

The constant term (338.34) of the recommended equation is significantly lower than that of any alternate choice of equations. The lower the constant term in a given equation, the more significant is the contribution to the relationship by the variables. In addition, the index stations (variables) in the recommended equation contribute more uniformly to the relationship (as evidenced by their regression coefficients, 0.955, 1.308, 1.237, 1.251, 0.830) than those of any alternate choice.

(b) Physical Significance

The five index stations all have significant flows during the irrigation season and, with the exception of Little Bow River below Travers Dam - 05ACO12, are situated within the L.N.I.D. so as to provide a fair areal representation of return flow (i.e., they are not clustered in a relatively small area - See PLATE 2). The flow at Little Bow River near the Mouth - 05ACO23 includes the flow at Little Bow River below Travers Dam - 05ACO12. The flow at Little Bow River below Travers Dam must therefore be subtracted to obtain return flow in the intervening reaches. In addition, the recommended equation results from the analysis of data from relatively dry (1972) and wet (1981) years. Having five, rather than fewer, index stations should prove advantageous during a future reassessment of the return flow estimates.

(c) Hydrometric

Of the five recommended index stations, four have been in existence for periods ranging from 10 to 27 years and are equipped with recording instruments. Together with the new station recommended for Drain L-5 near Diamond City, all are readily accessible during the irrigation season. Since four of the recommended index stations are presently in use for the determination of return flow there would be a net increase of one station.

Comparison Between Recommended and Previous (1974) Return Flow Equations

Table 4 shows the resulting standard error of estimate in percent when the recommended and previous (1974) regression equations are applied to each of the four years under consideration. It is evident that there is a significant improvement in return flow estimation for the later years, 1979 and 1981.

TABLE 4

COMPARISON BETWEEN RECOMMENDED AND PREVIOUS (1974) RETURN FLOW EQUATIONS

LETHBRIDGE NORTHERN IRRIGATION DISTRICT

Year Return Flow Equation	1971	1972	1979	1981
Standard Error of Estimate in Percent for the Recommended Equation	6.8	5.2	13.9	4.0
Standard Error of Estimate in Percent for the Previous (1974)* Equation	9.1	7.2	49.1	20.7

* 1974 Equation: Return Flow (Ac-Ft.) = 2546.6

+0.841 (Piyami Drain)

-0.800 (Little Bow River below Travers Dam)

+.800 (Little Bow River near the Mouth)

+0.994 (Battersea Drain)

5.2 St. Mary River Irrigation District (S.M.R.I.D.) and
Taber Irrigation District (T.I.D.)

Due to their proximity and apparent similarity in irrigation practices, the S.M.R.I.D. and T.I.D. were combined for the present analysis. The return flow data collected from the S.M.R.I.D. for the years 1971, 1972, 1979 and 1981 are included in the Appendix as Tables 71-2, 72-2, 79-2 and 81-2, and similarly, the data for the T.I.D. are included as Tables 71-3, 72-3, 79-3, and 81-3. The return flows selected as independent variables for the regression analysis are shown in Table 5 and were determined, and their monthly flow volumes derived, in the same manner as those for the L.N.I.D. analysis. Similarly, the combined S.M.R.I.D. and T.I.D. total return flows shown in Table 6 were used to generate the total return flow volumes in Table 7 which were used as the dependent variables in the regression analysis. In all, 24 data sets were derived for the analysis.

TABLE 5

SELECTED INDEPENDENT VARIABLES

ST. MARY RIVER IRRIGATION DISTRICT AND TAGER IRRIGATION DISTRICT

(All Figures in dam³)

Data sets derived for the years shown	1971						1972							
Indep. Variables (Return Flow Stations)	1	2	3	4	5	6	1	2	3	4	5	6	7	
Drain S-10 near Bow Island (05AJ003)	213	728	630	279	440	91	0	367	758	621	554	396	99	
I - Seven Persons Creek at Medicine Hat (05AH005)	2701	3148	3670	1013	2261	250	3421	4308	3618	2290	1593	1284	1949	
S-2 - Lateral 10 Spillway near Chin (05AG007)	132	228	440	316	198	12	379	352	516	0	372	15	15	
Drain S-4 near Grassy Lake (05AJ002)	617	478	197	815	213	7	531	213	690	516	455	1130	584	
S-5	411	167	1092	286	426	683	0	352	554	68	167	9	485	
S-6	4	796	296	110	15	296	4	14	303	364	303	154	137	
S-8	286	523	910	499	859	470	326	1020	0	545	683	73	167	
S-9	242	11	319	382	125	311	76	213	3	288	258	161	35	
S-11	125	212	152	161	206	159	220	440	387	129	281	235	0	
76	-	-	-	-	-	_		_	-	-		-	-	
S-17	106	26	41	0	1	311	220	301	83	64) 0	106	
II	1791	1138	2283	1402	1174	1100	713	2099	1016	827	1691	1512	538	
Bountiful Coulee near Cranford (05AGOO8)	1277	2101	1623	1028	903	774	758	2128	1418	1449	1418	228	690	
Drain T-2 near Taber (05AG023)	734	827	963	873	756	690	463	404	432	1130	921	286	394	
Drain T-11 near Fincastle (05AG025)	382	265	470	477	440	83	0	617	546	258	334	360	281	
Bountiful Coulee Inflow near Cranford (05AG026)	1198	1599	131	1285	44	1797	539	1221	737	1055	659	189	190	
T-1	369	675	660	418	705	940	-	440	827	1039	842	330	508	
T-3	3	114	584	389	807	751	660	719	1274	705	827	220	167	
1-8	242	212	190	316	417	34	523	26	311	174	538	132	410	
T-9	110	394	1251	352	462	341	0	235	0	15	728	389	349	
T-10	272	341	288	308	492	74	a	389	76	61	288	264	159	
T-13	250	379	1077	851	492	447	167	499	250	887	561	734	630	
58	-	-	-	-	-	-	-	-	-	-	-	-	-	
	L	<u> </u>	<u> </u>	<u> </u>	<u>L</u>			<u></u>	<u> </u>	<u> </u>				

TABLE 5 (continued)

SELECTED INDEPENDENT VARIABLES

ST. MARY RIVER IRRIGATION DISTRICT AND TABER IRRIGATION DISTRICT

(All Figures in dam³)

years shown			1	.979					1981	•	
Selected	 	 			r——				1201		
Indep. Variables (Return Flow Stations)	1	2	3	4	5	6	1	2	3	4	5
Drain S-10 near Bow Island (05AJ003)	1835	1637	1387	143	287	371	1390	1277	921	233	760
I - Seven Persons Creek at Medicine Hat (05AH005)	3955	4312	5051	2692	2750	2928	3447	4756	4250	3577	4261
S-2 - Lateral 10 Spillway near Chin (05AG007)	374	579	331	136	461	99	306	206	423	881	410
Drain S-4 near Grassy Lake (05AJ002)	374	601	1069	1095	98	622	610	727	845	610	358
S-5	677	541	600	865	88	589	1820	501	1195	1026	798
S-6	13	313	279	279	5	375	65	554	637	1 596	573
S-8	270	418	643	463	251	327	415	785	745	814	962
S-9	332	372	0	40	202	442	29	412	249	376	376
S-11	715	147	21	64	194	471	65	0	8	469	441
76	228	399	629	102	3	236	236	812	78	39	337
S-17	474	56	171	29	0	88	109	166	434	363	168
II	482	846	375	1773	884	2108	1278	1243	321	933	
Bountiful Coulee near Cranford (05AG008)	1434	1708	1716	1214	1275	630	1507	1390	1347	1407	1543
Drain T-2 near Taber (05AG023)	874	658	569	599	737	621	1100	970	1207	857	448
Drain T-11 near Fincastle (05AG025)	398	197	533	451	208	584	597	608	518	537	378
Bountiful Coulee Inflow near Cranford (05AG026)	1174	774	512	581	710	415	764	787	1027	1067	864
T-1	765	0	54	520	529	573	238	704	648	964	371
T-3	441	404	0	595	301	1173	277	621	252	594	137
T-8	430	56	150	828	669	1004	975	129	412	288	573
T-9	643	402	418	544	399	662	181	351	383	482	156
T-10	490	0	557	214	358	346	487	1229	485	531	456
T-13	1024	174	445	1093	964	415	365	720	849	373	1369
58	194	27	276	177	176	228	384	142	230	0	148

TABLE 6

COMBINED TOTAL RETURN FLOW

ST. MARY RIVER IRRIGATION DISTRICT AND TABER IRRIGATION DISTRICT

	1971	TOTAL RETU	RN FLOW (m	3/sec.)	·
JUNE	JULY	AUGUST	SEPTI	MBER	OCTOBER
17	13	· 4	1	21	13
4.906	6.197	-7.545	5.013	4.810	3.863

•		1972 TOTAL	RETURN FLO	W (m³/sec	:.)	
MAY	JUNE	JULY	AUGL	ST	SEPTEMBER	OCTOBER
25	13	11	1	29	26	17
3.506	6.584	5.921	5.560	5.421	4.005	3.107

	1979	TOTAL RETU	RN FLOW (m	3/sec.)	•
JUNE	JULY	AU	GUST	SEPTEMBER	OCTOBER
13	11	1	29	19	17
7.326	6.175	6.389	5.881	4.897	5.277

19	81 TOTAL R	ETURN FLOW	(m ³ /sec.)	· • · · · · · · · · · · · · · · · · · ·
JUNE	JULY	AUGUST	SEPTE	MBER
24	22	12	2	23
6.111	7.470	6.535	6.581	6.346

TABLE 7

DEPENDENT VARIABLE TOTAL RETURN FLOW FOR DATA SETS IN TABLE 6

ST. MARY RIVER IRRIGATION DISTRICT AND TABER IRRIGATION DISTRICT

(All Figures in dam³)

Data sets derived for the years shown	1971					1972							
Dependent Variables	1	2	3	4	5	6	1	2	3	4	5	6	7
Total Return Flow	12716	16598	20209	12994	12468	10347	9390	17066	15859	14892	14520	10381	8322

Data sets derived for the years shown	1979					1981					
Dependent Variables	1	2	3	4	5	6	1	2	3	4	5
Total Return Flow	18989	16539	17112	15752	12693	14134	15840	20008	17503	17058	16449

TABLE 8

REGRESSION ANALYSIS ST. MARY RIVER IRRIGATION DISTRICT AND TABER IRRIGATION DISTRICT

¢0	TRI MBINA			REGRESSION EQUATIONS	MULTIPLE CORRELAT'N COEFF.	STANDARD ERROR OF ESTIMATE (%)	DATA SETS USED IN ANALYSIS	INDEX STNS. REQ'D.
1971	1972	1979	1981	Y=924.57+1.788X1+2.515Xs+3.393X1++2.563X1s+1.231X17+2.128X1*	0.97	6.4	24	6
1971		1979	1981	Y=3340.62+1.824X1+4.328X6+5.739X13+2.452X17	0.95	6.4	17	4
1971	-	1979	1981	Y=4253.55+3.871X ₂ +1.460X ₃ +6.164X ₆ +4.381X ₁₃ +5.576X ₁₉	0.95	6.8	17	5
-	1972	1979	1981	Y=4668.78+1.988X ₆ +3.944X ₆ +5.640X ₁₂ +2.187X ₁₃ +7.965X ₁₇	0.98	5.4	18	5
1971	1972	-	1981	Y=2235.41+0.741x1+3.396X2+2.693X3+1.930X4+1.643X6+6.842X10 +3.180X13	0.99	5.1	18	7
1971	1972	-	1981	Y=4514.46+0.791X1+2.866X2+3.139X3+6.752X10+2.860X13	0.97	6.6	18	5
1971	1972	1979	-	Y=3988.36+3.026x2+3.790xs+2.394x1s+2.316x1s	0.96	6.9	19	4
-	1972	-	1981	Y=5795.22+2.666X ₃ +6.113X ₆ +6.866X ₁₀ +4.422X ₁₇	0.98	6.1	12	4
1971	-	-	1981	No Significant Equation			11	
1971	•	1979	-	Y=682.20+1.539X1+2.087X4+5.697X5+6.327X13+1.707X17	0.99	4.2	12	5
-	1972	1979	-	Y=1526.30+1.064X ₃ +3.306X ₆ +3.806X ₅ +8.300X ₆ +4.910X ₁₁ +4.820X ₁₇	0.99	5.1	13	6
-	1972	1979	-	Y=13.41+4.311X ₄ +4.796X ₅ +8.725X ₆ +6.619X ₁₂ +5.365X ₁₇	0.98	6.2	13	5
•	-	1979	1981	Y=7433.72+2.723X4+5.746X ₁₂ +1.157X ₁₄ +6.583X ₁₇	0.99	2.4	11	4
-	-	1979	-	No Significant Equation			6	

*Recommended Equation

```
X_1 = I - Seven Persons Creek at Medicine Hat (05AH005) X_2 * Bountiful Coulee near Cranford (05AG008) X_3 = Drain S-10 near Bow Island (05AJ003) X_4 = Drain S-4 near Grassy Lake (05AJ002) X_5 = Drain T-2 near Taber (05AG023) X_6 = Drain T-11 near Fincastle (05AG025) X_6 = T-3 X_{10} = S-9 X_{11} = S-2 - Lateral 10 Spillway near Chin (05AG007) X_{12} = 76 X_{13} = T-9 X_{14} = T-1 X_{15} = T-13 X_{17} = Bountiful Coulee Inflow near Cranford (05AG026) X_{18} = II X_{19} = 58
```

Table 8 shows the trial combinations of data sets used in the regression analysis. The computer programs previously referred to were applied and the recommended equation

$$(S.M.R.I.D. + T.I.D.)$$
 Monthly Return flow $(dam^3) = 924.57$

$$+ 1.788X_1 + 2.515X_3 + 3.393X_{14} + 2.563X_{15} + 1.231X_{17}$$

+ 2.128X₁₈

using monthly recorded flows (dam³) at the following index stations:

X₁ = Seven Persons Creek at Medicine Hat (05AH005)

 X_{3} = Drain S-10 near Bow Island (05AJ003)

 $X_{14} = T-1$

 $X_{15} = T-13$

 X_{17} = Bountiful Coulee Inflow near Cranford (05AG026)

 $X_{18} = II$

was chosen from Table 8 based on the following considerations:

(a) Statistical Signficance

Multiple Correlation Coefficient = 0.97

Coefficient of Determination = 0.94

Standard Error of Estimate = 6.4%

Student's "t"-test was applied to the regression coefficients of the recommended equation and the computed "t-values" were tested at the 95% confidence level.

Independent Variable	Regression Coefficient	<u>"t"</u>
x_1	1.788	8.38
x ₃	2.515	4.99
x ₁₄	3.393	4.33
x ₁₅	2.563	3.97
x ₁₇	1.231	2.57
x ₁₈	2.128	5.89

The minimum acceptable "t-value", at the 95% confidence level, is 2 and is exceeded for each of the regression coefficients.

The relative magnitude of the constant term and the relative contribution of each index station (variable) in the equation to the total result suggests a relationship superior to any reasonable alternate choice from Table 8.

(b) Phyical Significance

The six index stations all have significant flows during the irrigation season and are situated within the S.M.R.I.D. and T.I.D. so as to provide a fair areal representation of return flow. The recommended equation results from the analysis of all available data sets (13 from dry years 1971 and 1972 and 11 from normal years 1979 and 1981). Having six, rather than fewer, index stations should prove advantageous during a future reassessment of the return flow.

(c) Hydrometric

Three of the recommended index stations are presently in existence and have been equipped with recording instruments for 3 to 13

years. Together with the three proposed new stations at T-1, T-13 and II (Ross Creek near Medicine Hat), all are readily accessible during the irrigation season.

While use of the recommended equation would require the establishment of three new recording stations, it is likely that three of the present index stations (i.e., Bountiful Coulee near Cranford - 05AG008, Drain T-2 near Taber - 05AG023, Drain T-11 near Fincastle - 05AG025) would be discontinued and relocated to the new required sites. There would, therefore, be no net increase in the total number of stations.

Revision/Update

Subsequent to the recommendation of the new return flow equation for the S.M.R.I.D. and T.I.D., a final reconnaissance of the proposed new gauging sites revealed that a severe landslide had occurred in the only suitable area for a station on Drain T-13. Consequently, a further regression analysis was performed on data from the following combinations of years:

1971, 1972, 1979, 1981 - 24 data sets

1972, 1979, 1981 - 18 data sets

1971, 1979, 1981 - 17 data sets

1971, 1972, 1981 - 18 data sets

1971, 1972, 1979 - 19 data sets

By applying the previously mentioned criteria and excluding T-13 from the analysis, a satisfactory result was obtained from using the 18 data sets from 1972, 1979 and 1981:

(S.M.R.I.D. + T.I.D.) Monthly Return Flow $(dam^3) = 1554.1$

 $+ 1.558X_1 + 2.132X_3 + 2.106X_4 + 3.631X_{14} + 3.064X_{17}$

+ 1.322X₁₈

using monthly recorded flows (dam3) at the following index stations:

X₁ = Seven Persons Creek at Medicine Hat (05AH005)

 X_2 = Drain S-10 near Bow Island (05AJ003)

 X_h = Drain S-4 near Grassy Lake (05AJ002)

 $X_{14} = T-1$

 X_{17} = Bountiful Coulee Inflow near Cranford (05AJ026)

 $X_{18} = II$

The statistical characteristics of the equation are:

Multiple Correlation Coefficient = 0.97

Coefficient of Determination = 0.94

Standard Error of Estimate = 6.9%

Student's "t"-test was applied to the regression coefficients of the recommended equation and the computed "t-values" tested at the 95% confidence level were found significantly different from zero.

The revised equation makes use of one additional existing station (i.e., Drain S-4 near Grassy Lake - 05AJ002) in place of T-13, so that there remains the need to construct only two new stations, T-1 and II.

As before, it is recommended that the stations Bountiful Coulee near Cranford (05AG008), Drain T-2 near Taber (05AG023) and Drain T-11 near Fincastle (05AG025) be discontinued. There would, therefore, be a net decrease of one hydrometric station.

Comparison Between Recommended and Previous (1974) Return Flow Equations

Table 9 shows the resulting standard error of estimate in percent when the recommended and previous (1974) equations are applied to each of the four years under consideration. It is evident that there is a significant improvement in return flow estimation for all years 1971, 1972, 1979, and 1981.

TABLE 9

COMPARISON BETWEEN RECOMMENDED AND PREVIOUS (1974) RETURN FLOW EQUATIONS

ST. MARY RIVER IRRIGATION DISTRICT AND TABER IRRIGATION DISTRICT

Year Return Flow Equation	1971	1972	1979	1981
Standard Error of Estimate in Percent for the Recommended Equation	4.3	5.3	3.2	3.4
Standard Error of Estimate in Percent for the Previous (1974)* Equation	9.8	5.5	11.2	14.1

* 1974 Equation: Return Flow (Ac-Ft.) = 2467.8+1.252 (Bountiful Coulee near Cranford) +4.545 (Drain T-2 near Taber)

+6.913 (Drain T-11 near Fincastle) +3.165 (Drain S-10 near Bow Island) +0.841 (Seven Persons Creek at Medicine Hat)

5.3 Magrath Irrigation District (M.I.D.) and
Raymond Irrigation District (R.I.D.)

The return flow data collected from the M.I.D. for the years 1979 and 1981 is included in the Appendix as Tables 79-4 and 81-4. The only return flow data collected from the R.I.D. was that recorded by Pothole Creek at Russell's Ranch (05AE016) and is included in the Appendix as Tables 72-5, 79-5 and 81-5. As evidenced by field inspections and the data collected, more than 95% of the return flow from the M.I.D. and R.I.D. combined is accounted for by the two recording stations, Dry Coulee near Magrath (05AE041) and Pothole Creek at Russell's Ranch (05AE016). Therefore, it is recommended that, on a monthly basis, (M.I.D. + R.I.D.) Return Flow (dam³) = Monthly Recorded Flows at

(M.I.D. + R.I.D.) Return Flow (dam) = Monthly Recorded Flows at
Dry Coulee near Magrath (05AE041) + Pothole Creek at Russell's Ranch
(05AE016).

5.4 Mountain View, Leavitt, and Aetna Irrigation Districts

Data collected for the Mountain View Irrigation District for the years 1972, 1979, and 1981 are included in the Appendix as Tables 72-6, 79-6, and 81-6. No usable data could be found for the Leavitt or Aetna districts. Due to the relatively small diversion and consumptive use applicable to these irrigation districts, it would not likely be practical to establish index stations with a view to obtaining a satisfactory regression equation. Additionally, the significant amount of natural runoff in the return flow channels would make such a determination difficult. Consequently, Table 10 was prepared to show the measured return flow as a percentage of the recorded diversion at Mountain View Irrigation District Canal (05ADO17).

TABLE 10

CALCULATION OF RETURN FLOW AS A PERCENTAGE OF DIVERSION

MOUNTAIN VIEW IRRIGATION DISTRICT (M.V.I.D.)

(All Figures in m³/sec)

. Irrigation Season			19	72	•				19	79					1981		
Return Flow	June	Ju	ly	Sep	t.	Oct.	June	Ju	ly	Aug.	Sept.	Oct.	June .	July	Aug	ust	Sept.
Monitoring Dates	23 18 28 6 22 24	11	9	30	27	17	15	22	20	10	31	21					
Total Return Flow for each date from all M.Y.I.D. measurement sites shown in Tables 72-6;79-6;81-6.	. 448	.542	.139	.221	. 175	. 344	.122	.057	.015	.143	.100	0	.093	.105	.076	.093	.096
Total Diversion as recorded by Mountain View Irrigation District Canal (05ADO17)	.042	2.02	.484	1.36	1.15	.915	.070	3.37	.016	.391	1.58	.033	.088	.619	2.18	1.98	1.70
*Return Flow as a percentage of diversion	>100	26.8	28.7	16.3	15.2	37.6	>100	1.7	93.8	36.6	6.3	0	>100	17.0	3.5	4.7	5.7

^{*}Note that the M.V.I.D. Canal (05AD017) supplies the Leavitt and Aetna irrigation districts as well as the M.V.I.D., and since return flow for the Leavitt and Aetna districts is not accounted for, these figures are lower than actual.

Based on the limited data available and the calculation shown in Table 10, and partly on judgement, it is recommended that Mountain View, Leavitt and Aetna irrigation districts' monthly return flow be determined as a percentage of the respective monthly diversion recorded by the gauge on the Mountain View Irrigation District Canal (05AD017), as follows:

<u>May</u>	<u>June</u>	<u>July</u>	Aug.	<u>Sept.</u>	Oct.
100%	100%	40%	35%	20%	35 %

As for the United Irrigation District, the Mountain View, Leavitt and Aetna Irrigation districts receive significantly more precipitation and moisture from spring snowmelt than the irrigation districts to the east. As a result, irrigation from diversion tends to begin much later in the season; hence the 100% values shown for May and June.

5.5 United Irrigation District (U.I.D.)

The return flow data collected from the U.I.D. for the years 1979 and 1981 is included in the Appendix as Tables 79-7 and 81-7. The data was treated in a manner similar to that for the L.N.I.D., S.M.R.I.D. and T.I.D., and a "best possible" regression equation was obtained; however, a very high standard error of estimate resulted, likely due to the high proportion of natural flow in the return flow channels, and the equation was rejected. Table 11 was then prepared to show the measured return flow as a percentage of the recorded diversion at U.I.D. Canal near Hill Spring (05AD013).

TABLE 11

CALCULATION OF RETURN FLOW AS A PERCENTAGE OF DIVERSION

UNITED IRRIGATION DISTRICT (U.I.D.)

(All Figures in m³/sec)

Irrigation Season		1979					1981				
Return Flow	June Jul		ly Aug.		Sept.	Oct.	June	July	Aug	ust	Sept.
Monitoring Dates	11	9	30	27	17	15	22	20	10	31	21
Total Return Flow for each date from all U.I.O. measurement sites shown in Tables 79-7 and 81-7	. 137	.983	1.228	.592	.099	. 325	. 266	.670	.527	.717	.516
Total Diversion to the U.I.D. (United Irrigation District Canal - near Hill Spring OSADO13)	1.57	3.02	2.94	. 335	1.08	1.54	.066	1.74	2.04	1.87	1.89
Return Flow as a percentage of diversion	8.7	32.5	41.8	>100	9.2	21.1	>100	38.5	25.8	38.3	27.3

Based partly on the limited data available and the calculation described in Table 11, and partly on judgement, it is recommended that U.I.D. monthly return flow be determined as a percentage of the respective monthly diversion recorded by the gauge on the U.I.D. Canal near Hill Spring (05AD013), as follows:

May	<u>June</u>	<u>July</u>	Aug.	Sept.	Oct.
100%	100%	35%	30%	25 %	20%

The U.I.D. receives significantly more precipitation and moisture from spring snowmelt than irrigation districts to the east. As a result, irrigation from diversion tends to begin much later in the season; hence the 100% values shown for May and June.

-40-

6. BIBLIOGRAPHY

- 6.1 "Natural Flow Determination of Irrigation Return Flow in Southern Alberta". Technical Report to the PPWB Committee on Hydrology, Environment Canada, March 1974.
- 6.2 "MULCOR Multiple Correlations". IBM Scientific Subroutine Package, 1971.
- 6.3 "P9R All Possible Subsets Regressions". BMDP Statistical Software, University of California Press, Berkley, Los Angeles, 1981.

APPENDIX

-44-

-

TABLE 71-1

LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.)

1971 Return Flow Data

							1971	Retur	n Flow	(m ³ /s	ec)						 -
STATION		Ju	ne			July			August			Se	ptembe	r		Octo	ber
	14	22	23	24	15	16	19	6	9	10	1	3	22	23	24	14	15
I	.068				0				.009			.037	.045			. 130	
G G	0				0				0			o			0		0
F	0				0			ļļ.	0			.001			.001	į	.003
Ε	0				.004			 	a			0			0		0
D		l i	.031		0		!		.004			.016			.024	Ì	.045
c	.003				0				.045			.001			.001		.007
В	0				0				0			0			0		.003
L-1		.091					.015		.088			.091			.184		.127
L-2			.001		.004					.001		.031			.005		.006
L-3			0		.008					.001		0			.008		.045
L-4			0		.007					0	1	0			0		0
L-5			.167		.021					. 358		. 351			. 309		.085
L-6: Piyami Drain (05AD037)			. 402		.606					. 926		.549			.524		.521
L-7			.059		. 204					.177	}	.057			240		9-4
L-8			.015		0					0	ļ	0			. 348		. 309
L-9	İ		.127		.153										0		0
L-10			.008		.024					.022		.037			.008		.122
L-11			.018		.079				}	.043	1	1		<u> </u>	.004	1 1	0
L-12				.009	.073	.004		.007		.040	1	.004			.048		.034
Н	0			.003	a	.004		.007]		.009			.013		.003
			.001*		.001*			1	0	2014		0		0			.003
M			.001*		.003*					.001*		.001*				.001	
N.			.005*		.057*					.003*		.003*	.003			.001	
0			.391*		.926*					.057*		.057*				.005	
P			.002*		ll l					.926*		.926*				. 391	
Q			.002"		.110* 0*		:			.110*		.110*	.110			. 002	i
R			.001*		0*				İ	0*		0*	0			0	
S			.007*							0*		0*	0			.001	
T			.013*		.001* .024*					.001*	ĺ	.001	.001			.007	
			.001*		l i				İ	.024*		024*	.024			.013	
j v			.001*		.001* 0*					.001*		*100	.001			.001	
ا ن			-001*		-					0*		0*	0			0	
X			.040*		.001*				<u> </u>	.001*		.001*				.001	
Ŷ		1	.323*		.147				}	.178	.022	[.003			.040	
Z			.085*		.357*			. 357			. 343		. 323	}		. 323	
L-0	.009		.000*		.001*			.001			.074		.153			.085	
L-13:	.009						0		1	0	.013				.015]	.011
Battersea Drain (05ADO38)			. 241		.807			.419				.436			.909		.425
Estimated Additional Flows between L-1 & L-13			.016*		.007*				.016*			.016*			.008*		.034*
TOTAL for the period shown		2.13	36			.572			3.826		3.2	12		4.057		2.784	

*Estimated Values

TABLE 72-1

LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.)

1972 Return Flow Data

							1	972 Re	turn F	low (m	3/sec.)						
STATION	L	Ma	y			June		Ju	ly		A	ugust			Septe	mber	Octo	ber
	25	26	29	30	20	21	22	12	13	2	3	4	30	31	28	29	19	20
I			.010			.009		'	.028	1				.037		.009		.009
G		0			ļ	0			0	ļ	0			ļ		0		.003
F		.001				0			.001		0					.006		.006
Ε		.021]		.001			0		0					.004		0
D		.042				.005			.005	.024			-	.048		.045		.028
С] }	.024				.003			.004	.003						.007		.003
8		0				.005			.010	ĺ	0		Ï			.003		.004
L-1		!	.085			.119		.013			.071			.144		0	ļ	.042
L-2			0	i i		.048			.025	1	.010	}	i I	.008	0	}		0
L-3			0			.012			0		.008			0	0		.003	
L-4			0	ł i		0	}	0		1	.011]		0		0	0	
L-5 L-6:			. 439			.637		ļ !]	.280		.040			. 351	.597		. 195	
Piyami Drain (05AD037)			. 337			.762		!	.881		.566			.595	. 462		.453	
L-7]]		}	.161]	.136		,	.159	1	.184			.042	.235	,	. 351	
L-8			0			.001			0	ļ	0		ĺ	0	0		0	
L-9))		1	.008		.001			.031		.099		i	.054	.147		.003	
L-10				. 026		.010		'	0	ĺ	0			.003	0	1 1	0	
L-11			Ì	.003		.034			.021		0	Ì		.093	.010		.016	
L-12	1 (.003	(İ	}		.004	·	.003	ĺ		.007	} ;	.007	.005	} {	.007	
L-13: Battersea Drain (OSADO38)	. 331				,		. 396		. 651		 - 	. 609	. 447		. 595	 	. 266	
L-0)) }		0		ļ	0		.007			0		-	0		.045	ļ	.026
Estimated Additional Flow		.012*				. 022*			. 088*			110-						
between L-0 & L-13		.012				.022			.000			.119*		.062*		.010*		.053
J		0	Ì		}	0		0		0		1 1		.031	}	0	,	0
Little Bow Rivernear the Mouth (05ACO23)	2.72				2.367			1.795			2.274		1,747		1.339		1.294	
Minus]		}]	}	}						[
Little Bow River below Travers Dam (05ACD12) (see note)	-1.288					937		793			314		295		295		275	
TOTAL for the period Shown		2.93	35			3.635	-	3	. 209	<u> </u>	3.711		3.	374	3.	224	2.	487

*Estimated Values

NOTE: The difference in flows from Little Bow River below Travers Dam to Little Bow River near the Mouth is equivalent to the sum of flows for stations L through Z, shown in Table 71-1.

TABLE 79-1

LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.)

1979 Return Flow Data

		197	9 Return F	low (m ³ /se	c.)	
STATION	June	Ju	ly	Aug.	Sept.	Oct.
	12	10	31	28	18	16
I	0.072	0.013	0.001	0	0.004	0.023
G	0	0	0	0	0	0
F	0	0	0*	0.002	0	0
F-1	0	0	0	0	0	0
E	0	0	0.001*	0.007	0.002	0.060
D	0.007	0.006	0.007	0.014	0.003	0.021
С	0.072	0.037	0.005	0.003	0.001	0.004
В	0	0	0	0.002	0.002	0.001
7	0.077	0.175	0.185	0.252	0.054	0.069
1-A	0.015	0	0	0	0	0*
L-1	0.024	0*	0.024	0.133	0.027	0.131
L-2A	0*	0	0.001	0	0	0
L-2	0.033	0.013	0	0	0	0.001
L-3-1	0.001*	0	0	0.002	0	0.001*
L-3	0.055	0.019	0.001	0	0	0.001
L-3-2	0.001	0	0	0	0	0
L-4-A	0	0.005	0	0	0	0*
L-4	0.014	0.010	0	0.157	0.020	0.158
L-4-B	0	0.104	0.018	0	0	0
L-4-C	0	0	0	0	0	0
L-4-D	0	0	0	0	0	0
<u> </u>		· · · · · · · · · · · · · · · · · · ·			·	

TABLE 79-1 (cont'd)

LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.) 1979 Return Flow Data

		197	9 Return F	low (m³/se	c.)	
STATION	June	Ju	ly	Aug.	Sept.	Oct.
	12	10	31	28	18	16
L-5	0.119	0.103	0.001	0.118	0.009	0.028
L-5-A	0	0	0	0.001	0	0.001*
L-5-A-1	0	0	0	0.014	0	0
L-5-A-2	0	0	0	0.014	0	0
8-A	0	0	0	0	0.023	0
8	0	0	0	0	0	o
9	0.044	0.028	0	0	0	0
10	0	0	0	0	. 0	0
10-A	0	0*	0	0	0	0
11	0	0	0	o.	0	0
12	0	0	0	0	0	0
L-6: Piyami Drain (05AD037)	0.511	0.441	0.172	0.524	0.216	0.232
15	0	0	0	0	0	0
16	0	0	0	0	0	0
L-7	0.104	0.029	0.002	0.014	0.004	0.028
17	0.014	0	0	0	0	0
17-A	0	0	0	0	0	0
L-8	0.141	0	0	0	0	0
L-8-A	0	0	0	0	0	0
18	0	0	0	0	0	0

TABLE 79-1 (cont'd)

LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.) 1979 Return Flow Data

		197	9 Return F	low (m ³ /se	:c.)	
STATION	June	Ju	ly	Aug.	Sept.	Oct.
	12	10	31	28	18	16
18-A	0	0	0	0	0.001	0
20	0	0	` 0	0	0	0
21	0	0	0	0	0	0
23	0	0	0	0	0	0
L-9	0.047	0.054	0.001	0.028	0.012	0.002
26	0	0	0	0	0	0
28	0.008	0	0	0	0	0
28-1	0	0	0	0	0	0
28-2	0	0	0	0	0	0
29	0	0	0	0	0.001	0
L-10	0.020	0.015	0	0	0.002	0.109
31	0	0	0	0	0	0
32	0	0	0.001	0	0	0
L-11	0.011	0	0	0.002	0.006	0
36	0	0	0	0	0	0
L-12	0.005	0.012	0	0	0.002	0.001
39	0.010	0.001	0	0	0.001	0
40	0	0	0	0	0	0
L-13: Battersea Drain (05AD038)	0.522	0.164	0.094	0.482	0.440	0.523
41	0	0	0	0	0	0

TABLE 79-1 (cont'd)

LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.) 1979 Return Flow Data

	1979 Return Flow (m ³ /sec.)								
STATION	June	Ju	ly	Aug.	Sept.	Oct.			
	12	10	31	28	18	16			
41-A	0	0	0	0.001*	0	0			
41-B	0	0.012	0	0.002	0	0.003			
Little Bow River near the Mouth (05ACO23)	1.25	0.721	0.579	1.42	1.09	1.09			
Minus Little Bow River Below Travers Dam (05ACO12) (See Note)	-0.385	-0.489	-0.544	-0.473	-0.399	-0.343			
TOTAL for Period Shown	2.792	1.473	0.549	2.719	1.491	2.144			

*Estimated Values

NOTE: The difference in flows from Little Bow River below Travers Dam to Little Bow River near the Mouth is equivalent to the sum of flows for Stations L through Z, shown in Table 71-1.

TABLE 81-1

LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.)

1981 Return Flow Data

		1981 Retu	rn Flow (m	³ /sec.)	
STATION	June	July	Aug.	Sept	ember
	23	21	ון	1	22
I	Q.	0.008	0.001	0	0.071
G	0	0 -	0	0.001	0
F	0	0	0	0	0
F-1	0	0	0.002	0.003	0.003
E	0	0.070	0.006	0.006	0.005
D	0.017	0.050	0.029	0.007	0.026
С	0.009	0.060	0.005	0.016	0.003
В	0.001	0.029	0.002	0.004	0.001
ı	0.061	0.220	0.143	0.005	0.003
1-A	0	0	0	0	0
L-1	0	0	0.075	0.050	0.041
L-2-A	0	0	0	0.001	0
L-2	0	0.011	0.001	0.018	0
L-3-1	0	0.011	0.001	0	0*
L-3	0*	0	0	0	0
L-3-2	0	0	0	0	0
L-4-A	0	0	0	0	0
L-4	0	0.067	0.432	0.182	0.086
L-4-B	0.026	0	0	0	0
L-4-C	0	0	0*	0	0

LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.)

1981 Return Flow Data

TABLE 81-1 (cont'd)

		1981 Retu	rn Flow (m	3/sec.)	
STATION	June	July	Aug.	Sept	emb e r
	23	21	11	1	22
L-4-D	0	0	0.014	0	0
L-5	0	0.057	0.085	0.097	0.076
L-5-A	0	0	0	0	0
L-5-A-1	0	0	0	0	0
L-5-A-2	0	0	0	0	0
8-A	0	0	0	0	0
8	0.007	0.031	0.086	0	0.093
9	0	0.008	0.007	0	0
10	0	0	0.014	0	0.002
10-A	0	0	0	0	0
11	0	0	0	0	0
12	0	0	0	0	0
L-6: Piyami Drain (05AD037)	0.435	0.674	0.426	0.613	0.425
15	0	0	a	0	0
16	0	0	0	0	0
L-7	0.008	0.021	0.068	0.068	0.039
17	0	0	0	0	0
17-A	0	0	0	0	0
L-8	0	0	0	0	0

TABLE 81-1 (cont'd)

LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.) 1981 Return Flow Data

		1981 Retu	rn Flow (m	3/sec.)	
STATION	June	July	Aug.	Sept	ember
	23	21	11	1	22
L-8-A	0	0	0	0	0
18	0	0	0	0	0
18-A	0	0	0	0	0
20	0	0	0	0	0
21	0	0	0	0	0*
23	0	0	0	0	0
L-9	0.025	0.203	0.079	0.040	0
26	0	0	0	0	0
28	0	0	0	0	0
28-1	0	0	0	0	0
28-2	0	0	0	0	0
29	0	0	0	0	0
L-10	0.001	0.002	0.005	0.004	0
31	0	0	0	0	0
32	0	0	0	0	0
L-11	0	0	0	0.011*	0
36	0	0.003	0.001	0*	0
L-12	0.014	0.002	0.001	0.001	0.003
39	0.014	0.002	0.002	0.001*	0.002
40	0	0	0	0	0

TABLE 81-1 (cont'd)

LETHBRIDGE NORTHERN IRRIGATION DISTRICT (L.N.I.D.) 1981 Return Flow Data

		1981 Retu	rn Flow (m	3/sec.)	
STATION	June	July	Aug.	Sept	ember
	23	21	11	1	22
L-13: Battersea Drain (05AD038)	0.265	0.531	0.489	0.595	0.759
41	0	0	0	0	0
41-A	0	0	0.002	0	0
41-B	0.007	0.003	0.002	0.001*	0.003
Little Bow River near the Mouth (05ACO23)	1.70	2.36	2.73	2.13	1.84
Minus Little Bow River bel. Travers Dam (05ACO12) (See Note)	-1.07	-1.03	-1.04	-1.09	-1.03
TOTAL for Period Shown	1.520	3.400	3.694	2.755	2.479

^{*}Estimated Values

NOTE: The difference in flows from Little Bow River below Travers Dam to Little Bow River near the Mouth is equivalent to the sum of flows for Stations L through Z, shown in Table 71-1.




TABLE 71-2 ST. MARY RIVER IRRIGATION DISTRICT (S.M.R.I.D.) 1971 Return Flow Data

	1971 Return Flow (m³/sec.)							
STATION	JUNE	JULY	AUGUST	SEPT	SEPTEMBER			
	17	13	4	1	21	13		
Six Mile Coulee Spillway near Lethbridge (05ADO2O)	. 300	.283	.317	. 198	.159	.193		
S-1	.037	0	0	o	0	o		
S-2 Lateral-10 Spillway near Chin (OSAGOO7)	.051	.085	.164	. 122	.076	.005		
S-3	.048	.065	.059	. 042	.048	.085		
Drain S-4 near Grassy Lake (05AJ002)	.238	.178	. 074	. 314	.082	.003		
S-5	.159	.052	. 408	.110	.164	.255		
S-6	.001	.297	.110	.042	.006	.110		
S-7	.003	. 006	.011	.007	.014	.018		
S - 8	.110	.195	. 340	.193	, 331	.176		
S-9	.093	.004	.119	.147	.049	.116		
Drain S-10 near Bow Island (05AJ003)	.082	.272	. 235	.108	.170	.034		
S-11	.048	. 079	.057	.062	.079	.059		
\$-12	.093	.073	.167	.057	0	0		
S-13	. 150	.278	.227	.071	.133	.028		
S-14	0	.065	.065	.001	0	.028		
S-14-A	0	.003	.027	.020	. 054	.003		
S-15	0	.013	0	. 001	.001	0		
S-16	0	.009	.006	. 034	.003	.005		
S-17	040	.010	.015	0	.001	.116		
S-18	.002	.028	.003	. 034	. 099	.037		
I-Seven Persons Creek at Medicine Hat (05AH005)	1.042	1.175	1.416	. 391	.872	.093		
II.	. 691	. 425	. 852	.541	. 453	.411		
III*	328	099	085	074	-,127	150		
IA+	004	007	002	001	006	003		
γ *	-0	-0	-0	-0	001	-0		
Estimated Additional Flow between S-1 & S-18	.002	.001	. 025	.031	.001	0		
TOTAl for the Period Shown	2.858	3.500	4.610	2.451	2.661	1.622		

^{*[}II, IV and V are natural flow stations. Return flow at II = Flow at II - Flow at IV Return flow at I = Flow at I - Flow at V.

TABLE 72-2

ST. MARY RIVER IRRIGATION DISTRICT (S.M.R.I.D.)

1972 Return Flow Data

	1972 Return Flow (m ³ /sec.)								
STATION	MAY	JUNE	JULY	AUGUST		SEPTEMBER	OCTOBER		
	25	13	11	1	29	26	17		
Six Mile Coulee Spillway near Lethbridge (05AD020)	.011	. 295	.207	. 360	.210	.031	. 057		
5-1	.037	0	o	0	0	0	0		
S-2: Lateral-10 Spillway near Chin (05AG007)	. 142	. 136	. 193	0	.139	.006	.006		
S-3	0	.002	.001	.020	.003	.002	. 027		
Drain S-4 near Grassy Lake (05AJ002)	.198	. 082	. 258	.193	.170	.436	.218		
S-5	0	.136	.207	.025	.062	.003	. 181		
S-6	.001	. 005	.113	.136	.113	.059	.051		
S-7	.006	.012	.023	.009	.019	.009	.006		
S-8	.122	. 394	0	.204	.255	.028	.062		
S-9	.028	. 082	.001	.108	.096	.062	.013		
Drain S-10 near Bow Island (05AJ003)	0	. 142	.283	.232	.207	.153	.037		
S-11	. 082	.170	.144	. 048	. 105	.091	0		
S - 12	.011	.009	0	.040	.016	.021	0		
\$-13	0	0	.127	.195	0	.110	.062		
S-14	0	0	0	∥ 0	.051	.007	.009		
S-14-A	. 034	.110	.054	.136	.096	.623	.001		
S-15	.001	0	∥ 0	0	0	.015	.003		
S-16	.001	0	.004	.006	.012	.003	.003		
S-17	.082	.116	.031	.024	0	0	.040		
S-18	.034	. 099	.004	.074	.007	.144	.008		
I - Seven Persons Creek at Medicine Hat (05AH005)	1.277	1.662	1.351	.855	. 595	. 496	.728		
II	.266	.810	.379	. 309	.631	. 583	.201		
III*	091	513	079	054	059	099	110		
IV*	016	010	004	006	001	012	005		
V*	-0	-0	001	 	-0	√ -0	-0		
Estimated Additional Flows Between S-1 and S-18	.042	. 159	0	.004	.007	. 002	.010		
TOTAL for the Period Shown	2.268	3.898	3.296	2.918	2.734	2.773	1.608		

^{*} III, IV and V are natural flow stations. Return Flow at II = Flow at II - Flow at IV. Return Flow at I = Flow at I - Flow at V.

TABLE 79-2

ST. MARY RIVER IRRIGATION DISTRICT (S.M.R.I.D.)

1979 Return Flow Data

	1979 Return Flow (m ³ /sec.)						
STATION	JUNE	JULY	AUGUST		SEPTEMBER	OCTOBER	
	14	12	2	30	20	18	
Six Mile Coulee Spillway near Lethbridge (05A0020)	. 297	.401	. 312	. 213	.059	.056	
6, 7, 13, 19, 22, 24, 25	0	0	0	0	0	0	
27	0	.001	0	0	0	0	
30, 33, 35, 37	0	0	٥	0	0	0	
S-2 Lateral-10 Spillway near Chin (05AG007)	.144	.216	.124	.051	.179	.037	
S-3	0	0	.001	.200	.029	0	
Drain S-4 near Grassy Lake (05AJ002)	.144	.224	. 399	. 409	.037	. 232	
\$-5	. 261	.202	.224	. 323	.034	.220	
S-6	.005	.117	.104	.104	.002	.140	
S-7	.101	.010	.013	. 005	.008	.017	
S-8	.104	. 156	.240	.173	.097	.122	
71-1	.001	0	0	. 002	.001	.001	
72	0	0	0	0	0	0	
S-9	.128	.139	0	.015	.078	.165	
73	0	0	0	0	0	0	
Drain S-10 near Bow Island (05AJ003)	. 708	.611	.518	.053	.111	.139	
S-11	.276	.055	.008	.024	.075	.176	
S-12	.026	.096	.039	0	. 0	.051	
S-12-A	.023	0	0	0	0	0	
76	.088	.149	.235	.038	.001	.088	
76-1	0	0	0	0	0	0	
S-13	0	0	.035	0	0	0	
S-14	0	0	0	.002	.081	0	
S-15-A	0	0	.015	0	.007	0	
76-3	0	0	0	0	.005	0	
76-4	0	0	0	0	0	0	
77	.014	0	.015	.020	.028	0	
77-A	0	0	.020	0	0	0	
77 - 8	0	0	.020	0	0	0	
78	.006	0	0	0	0	0	
79	0	.001	0	0	0	0	
S-15	.001	0	.001	.018	0	.001	
S-16	0	0	. 034	.001	.001	.001	
S-17	. 183	.021	.064	.011	0	.033	
S-18	.037	.109	.002	.002	.147	.065	
I-Seven Persons Creek at Medicine Hat (05AH005)	1.53	1.61	1.89	1.01	1.06	1.09	
II	.186	.316	.140	. 662	. 341	. 787	
III*	064	-0	073	020	010	644	
IV*	005	010	002	010	007	007	
ν*	005	-0	005 `	001	-0	-0	
TOTAL for the Period Shown	4.189	4.424	4.373	3.305	2.364	2.770	

^{*}III, IV, and V are natural flow stations.

Return Flow at II = Flow at II - Flow at IV.

Return Flow at I = Flow at I - Flow at V.

TABLE 81-2

ST. MARY RIVER IRRIGATION DISTRICT (S.M.R.I.D.)

1981 Return Flow Data

	1981 Return Flow (m ³ /sec.)					
STATION	JUNE JULY		AUGUST	SEPTEMBER		
	25	22	12	3	24	
Six Mile Coulee Spillway near Lethbridge (05AD020)	Discont	d prior to	·			
6	0	.001	0	0	0	
7	0	0	0	0	0	
13	0	0	.003	0	0	
19, 22, 24, 25, 27, 30, 33, 35 37	0	0	o	0	0	
S-2: Lateral-10 Spillway near Chin (05AG007)	.118	. 077	. 158	. 340	. 158	
S-3	. 104	. 094	.040	.013	.015	
Drain S-4 near Grassy Lake (05AJ002)	.235	.271	.315	. 235	.138	
S-5	. 702	. 187	. 446	. 396	.308	
S-6	.025	.207	.238	.230	.214	
S-7	.006	0	.007	.005	.010	
S-8	.160	.293	.278	.314	. 371	
71-1	.001	0	0	.001	0	
72	0	0	0	0	0	
S - 9	.011	.154	.093	.145	.145	
73	0	0	0	0	0	
Drain S-10 near Bow Island (05AJ003)	.536	.477	.344	.090	.293	
S-11	.025	0	.003	. 181	.170	
S-12	.076	1 o	0	.005	0	
S-12-A	0	.045	.041	.001	0	
76 .	.091	.303	.029	.015	. 130	
76-1	0	.001	.001	.007	0	
S-13	.025	.042	0	.002	.002	
S-14	0	0	0	0	0	
S-15-A	∥ o	0	0	0	.001	
76- 3	0	0	0	0	0	
76-4	∥ 0	0	0	.001	0	
7 7	.089	.014	.021	.001	.001	
77 - A	0	0	.014	. 075	0	
77-B	0	0	0	0	0	
78	0	.039	0	0	0	
79	.028	.035	0	0	0	
S-15	0	0	.001	0	0	
\$-16	.002	0	0	0	.001	
S-17	.042	.062	.162	.140	.065	
S-18	.056	0	0	0	0	
I - Seven Persons Creek at Medicine Hat (05AH005)	1.33	1.78	1.59	1.38	1.64	
II	.493	.464	. 120	. 360	.419	
III*	472	014	020	005	010	
IV*	012	003	-0	002	001	
V*	-0	-0	-0	013	003	
TOTAL for the Period Shown	3.671	4.529	3.884	3.917	4.067	

^{*} III, IV and V are natural flow stations. Return Flow at II = Flow at II - Flow at III - Flow at IV. Return Flow at I = Flow at I - Flow at V.

TABLE 71-3

TABER IRRIGATION DISTRICT (T.I.D.)

1971 Return Flow Data

		1:	971 Return F	low (m³/sec.)		
STATION	JUNE	JULY	AUGUST	SEPT	EMBER	OCTOBER
	17	13	4	1	21	13
Bountiful Coulee near Cranford (05AG008)	.493	.784	. 606	. 396	. 348	. 289
Bountiful Coulee Inflow near Cranford (05AG206)	.461	. 598	. 048	.499	. 017	.671
T-1	. 142	.252	.246	.161	. 272	. 351
Orain T-2 near Taber (05AG023)	. 283	. 309	. 360	. 337	. 292	.258
T-3	.001	.042	.218	.150	.311	. 280
T-4	.071	ď	.045	.001	.001	.001
T-5	.074	0	.006	0	.006	.003
T-6	.015	.034	.057	.001	0	.006
T-7 ·	0	.079	.068	.040	.028	.001
T-8	.093	.079	.071	. 122	. 156	.013
T-9	.042	.147	.467	.136	.178	.127
T-10	.105	. 127	.108	.119	.019	.028
Drain T-11 near Fincastle (05AG025)	.147	.099	. 176	. 184	.170	.031
T-12	.021	0	∦ 0	0	.127	.015
T-13	.096	.142	.402	. 328	. 190	.167
Estimated Additional Flow between T-1 and T-13	. 004	.005	.057	.088	.034	0
TOTAL for the Period Shown	2.048	2.697	2.935	2.562	2.149	2.241

TABLE 72-3

TABER IRRIGATION DISTRICT (T.I.D.)

1972 Return Flow Data

			1972 Retui	rn Flow (m ³ /	sec.)		
STATION	MAY	JUNE	JULY	AUGU	ST	SEPTEMBER	OCTOBER
	25	13	11	11	29	26	17
Bountiful Coulee near Cranford (05AG008)	. 283	.821	.530	. 541	.530	.088	.258
Bountiful Coulee Inflow near Cranford (O5AGO26)	.201	.470	.274	. 393	. 246	.073	.070
T-1	0	.170	. 309	. 388	.314	.127	. 190
Drain T-2 near Taber (05AG023)	.173	. 156	. 161	. 422	. 348	.110	.147
T-3	.246	.278	. 476	.263	. 309	. 085	.062
T-4	.010	.013	.007	.074	.001	. 005	.003
T-5	.001	.010	.004	.004	.001	.003	.003
T-6	.051	0	.019	.010	0	.001	.001
T-7	.016	.037	.042	.017	. 007	.008	.012
T-8	.195	.010	.116	.065	.201	.051	.153
T-9	0	.091	0	.006	.272	.150	.130
T-T0	0	. 150	.028	.023	.108	. 102	.059
Drain T-11 near Fincastle (05AG024)	0	.238	.204	.096	.125	.139	.105
T-12	0	.009	0	0	.015	.007	.003
T-13	.062	.193	.093	.331	.201	. 283	. 235
Estimated Additional Flows Between T-1 and T-13	0	.040	. 362	.009	0	0	.068
TOTAL for the Period Shown	1.238	2.686	2.625	2.642	2.687	1.232	1.499

TABLE 79-3

TABER IRRIGATION DISTRICT (T.I.D.)

1979 Return Flow Data

	1979 Return Flow (m³/sec.)								
STATION	JUNE	JULY	AUG	UST	SEPTEMBER	OCTOBER			
	13	11	1	29	19	17			
Bountiful Coulee near Cranford (05AG008)	.553	.638	.641	. 453	. 492	. 235			
Bountiful Coulee Inflow near Cranford (05AG026)	. 453	.289	.191	.217	.274	. 155			
T-1	. 295	0	.020	.194	. 204	.214			
Orain T-2 near Taber (05AGO23)	. 337	.246	.212	.224	. 284	.231			
T-3	.170	.151	0	.222	.116	.438			
T-4	.025	0	o	0	0	0			
T-4-A	0	o	.023	0	O	0			
T-5	.001	.005	.001	.006	.001	.001			
T-6	.001	.009	0	0	0	0			
50	0	0	0	a	0	0			
51-A	0	0	0	.021	.008	a			
51	0	o	o	0	0	0			
T-7	0	a	0	0	0	i -			
52	a	0	a	0	0	0			
T-8	.166	.021	.056	. 309	. 258	0			
52-2	0	0	0	0	ľ	. 375			
T-9	.248	.150	.156		0	0			
T-10	.189	.130	1	.203	.154	.247			
55	0	0	.208	.080	.138	.129			
Orain T-11 near	.154	.074	.199	.168	.080	.218			
Fincastle (05AGD25) 57					1				
58	0	0	0	.001	.002	.008			
- I	.075	.010	.103	.066	.068	.085			
58-A	0	.021	.012	0	.012	0			
58-B	0	0	.007	0	.001	.001			
58-C 58-D	0	0	0	0	.004	.001			
	0.75	0	٥	0	0	0			
T-12	.075	0	0	0	0	0			
T-13	. 395	.065	.166	.408	. 372	.155			
61	0	0	0	0	0	0			
61-A	0	0	.001	0	0	0			
62	0	.036	.020	. 002	.065	.014			
62-A	0	0	0	0	0	0			
62-B	0	0	0	0	0	0			
62-C	0	.035	0	-002	0	0			
63	0	0	0	0	0	0			
64	0	0	0	0	0	0			
65	0	.001	0	0	0	0			
TOTAL for the Period Shown	3,137	1.751	2.016	2.576	2.533	2.507			

TABLE 81-3

TABER IRRIGATION DISTRICT (T.I.D.)


1981 Return Flow Data

		1981 Re	1981 Return Flow (m³/sec)								
STATION	JUNE	JULY	AUGUST	SEPT	EMBER						
	24	22	12	2	23						
Bountiful Coulee near Cranford (05AG008)	. 581	.519	. 503	. 543	. 595						
Bountiful Coulee Inflow near Cranford (05A G 026)	. 295	.294	. 383	.412	. 333						
T-1	. 092	. 263	. 242	. 372	. 143						
Orain T-2 near Taber (05AG023)	. 424	. 362	.451	. 331	. 173						
T-3	. 107	.232	.094	.229	.053						
T-4	. 02 6	0	.001	0	0						
T-4-A	0	0	0	0	0						
T-5	.001	.016	.023	.005	.005						
T-6	0	.001	0	0	0						
50	0	0	0	0	0						
51 - A	.004	.003	0	0	0						
51	0	0	0	0	0						
T-7	0	0	0	0	0						
52	0	o i	0		0						
T-8	0	0	0	0	0						
52-2	0	0	0	0 1	0						
T-9	.070	.131	.143	.186	.060						
T-10	. 188	. 459	.181	.205	.176						
55	0	0	0	0	0						
Drain T-11 near Fincastle (05AG025)	. 230	. 227	. 193	. 207	. 146						
57	.007	-001	.002	.005	a						
58	.148	.053	.086	0	. 057						
58-A	0	0	0	0	0						
58-8	.001	.001	0	.001	0						
58-C	.034	.042	.018	0	0						
58 -0	0	.001	0	0	0						
T-12	0	0	0	0	.004						
T-13	.141	. 269	. 317	.144	. 528						
61	0	0	0	0	0						
61-A	0	0	0	0	0						
62	.022	0	0	0	0						
62-A	0	0	0	0	0						
62-B	0	0	0	0	0						
62-Ç	0	0	0	0	0						
63	0	0	0	0	0						
64	0	0	0	,024	0						
65	.069	. 067	.014	0	.006						
TOTAL for the Period Shown	2.440	2.941	2.651	2.664	2.279						

ST. MARY RIVER IRRIGATION DISTRICT - WEST

NOTE


MAP COURTESY OF ALBERTA AGRICULTURE PRRIGATION DIVISION, LETHBRIDGE, ALTA.




TABER IRRIGATION DISTRICT

<u>NO</u>TE

MAP COURTESY OF ALBERTA AGRICULTURE IRRIGATION DIVISION, LETHBRIDGE, ALTA.







ST. MARY RIVER IRRIGATION DISTRICT - EAST

NOTE

MAP COURTESY OF ALBERTA AGRICULTURE IRRIGATION DIVISION, LETHBRIDGE, ALTA.




TABLE 79-4

MAGRATH IRRIGATION DISTRICT (M.I.D.)

1979 Return Flow Data

		1979 Return Flow (m³/sec.)								
STATION	JUNE	IE JULY		AUGUST	SEPTEMBER	OCTOBER				
	11	9	30	27	17	15				
MG-1: Bry Coulee near Magrath (05AE041)	.160	. 328	. 298	.250	. 021	.113				
MG-2	.001	. 005	.003	.002	0	.001				
MG-3	.004	0	0	0	0	0				

TABLE 81-4

MAGRATH IRRIGATION DISTRICT (M.I.D.)

1981 Return Flow Data

	1981 Return Flow (m ³ /sec.)							
STATION	JUNE	JULY	AUGU	ST	SEPTEMBER			
	22	20	10	31	21			
MG-1: Dry Coulee near Magrath (05AE041)	. 400	. 427	.133	. 133	.216			
MG-2	.007	.014	.010	.002	.003			
MG-3	0	.003	0	.001	0			

TABLE 72-5

RAYMOND IRRIGATION DISTRICT (R.I.D.)

1972 Return Flow Data

		1972 Return Flow (m³/sec.)								
STATION	MAY	JUNE	JU	ILY	SEPTE	MBER	OCTOBER			
	31	19	14	28	5	22	23			
Pothole Creek at Russell's Ranch (OSAEO16)	. 751	.691	.813	. 791	.697	.784	.059			

TABLE 79-5

RAYMOND IRRIGATION DISTRICT (R.I.D.)

1979 Return Flow Data

		1979 Return Flow (m ³ /sec.)								
STATION	JUNE JULY		AUGUST	SEPTEMBER	OCTOBER					
	11	9	30	27	17	15				
Pothole Creek at Russell's Ranch (OSAEO16)	. 496	.207	. 169	. 291	0	. 360				

TABLE 81-5

RAYMOND IRRIGATION DISTRICT (R.I.D.)

1981 Return Flow Data

	1981 Return Flow (m ³ /sec.)							
STATION	JUNE	JULY	AUGUST		SEPTEMBER			
	22	20	10	31	21			
Pothole Creek at Russell's Ranch (05AE016)	. 636	. 674	. 709	.280	. 379			

MAGRATH AND RAYMOND IRRIGATION DISTRICTS

NOTE

MAP COURTESY OF ALBERTA AGRICULTURE IRRIGATION DIVISION, LETHBRIDGE, ALTA.




PLATE No. 7

MOUNTAIN VIEW IRRIGATION DISTRICT (M.V.I.D.)

1972 Return Flow Data

		1972 Return Flow (m³/sec.)							
STATION	JUNE JULY		LY	SEPTEMBER		OCTOBER			
	23	18	28	6	22	24			
M-1	.413	.314	.028	.283	.122	. 328			
M-2	.004	.018	.011	.006	.006	.016			
*M-3	. 266	.042	.013	.133	.027	.034			
M-4	.297	. 252	.113	. 065	.074	. 034			

* Natural Flow.

Natural riow. NOTE: M-3 is situated upstream from M-1 on the same channel. Therefore, if the flow at M-3 is larger than that for M-1, the return flow in that channel = 0; otherwise, the return flow = M-1 - M-3.

TABLE 79-6

MOUNTAIN VIEW IRRIGATION DISTRICT (M.V.I.D.)

1979 Return Flow Data

STATION	1979 Return Flow (m ³ /sec.)							
	JUNE JULY		LY	AUGUST		OCTOBER		
	11	9	30	27	17	15		
1-1	. 485	.181	. 132	.180	105	0		
1-2	. 005	.002	.001	.001	0	0		
1-3 *	.511	.150	.122	.038	.005	.033		
4-4	.117	.024	.004	0	0	0		
	1-1 1-2 1-3*	11 .485 1-2 .005 1-3* .511	JUNE JUNE JUNE 11 9 1-1 .485 .181 1-2 .005 .002 1-3* .511 .150	JUNE JULY 11 9 30 1-1 .485 .181 .132 1-2 .005 .002 .001 1-3* .511 .150 .122	JUNE JULY AUGUST	JUNE		

NOTE: M-3 is situated upstream from M-1 on the same channel. Therefore, if the flow at M-3 is larger than that for M-1, the return flow in that channel = 0; otherwise, the return flow = M-1 - M-3.

TABLE 81-6

MOUNTAIN VIEW IRRIGATION DISTRICT (M.V.I.D.)

1981 Return Flow Data

	1981 Return Flow (m ³ /sec.)						
STATION	JUNE	JULY	AUGUST		SEPTEMBER		
	22	20	10	31	21		
M-1	.796	.206	.104	.154	.176		
M-2	.007	.004	.001	0	.001		
*M-3	.749	. 181	.036	.061	.081		
M-4	.039	.076	.007	a	•		

* Natural Flow

NOTE: M-3 is situated upstream from M-1 on the same channel. Therefore, if the flow at M-3 is larger than that for M-1, the return flow in that channel = 0, otherwise, the return flow = M-1 - M-3.

TABLE 79-7

UNITED IRRIGATION DISTRICT (U.I.D.)

1979 Return Flow Data

STATION		1979 Return Flow (m ³ /sec.)						
	JUNE	JUNE JULY		AUGUST	SEPTEMBER	OCTOBER		
	11	9	30	27	17	15		
U-1	.002	. 758	.710	.571	.021	.130		
U-1-A	0	0	0	0	0	0		
*U-2	.086	.102	. 324	.011	0	.163		
U-2-A	0	0	0	0	0	0		
U-2-8	0	0	0	0	0	0		
U-2-C	0	0	0	0	0	0		
U-3	.004	0	.002	.001	.001	0		
U-4	.018	.001	.002	0	0	0		
U-4-A	.010	0	.094	0	.002	.032		
U-4-B	0	0	0	0	0	0		
*U+5	.014	.113	.044	.003	.074	0		
U-5-A	0	0	.004	0	0	0		
U-5-8	0	0	.004	.004	.001	0		
U-6	. 003	.009	.044	.002	o	0		

^{*} Adjusted for Natural Flow

TABLE 81-7

UNITED IRRIGATION DISTRICT (U.I.D.)

1981 Return Flow Data

		1981 Return Flow (m ³ /sec.)						
STATION	JUNE	JULY	AUGUST		SEPTEMBER			
	22	20	10	31	21			
U-1	. 228	.459	.223	. 497	. 383			
U-1-A	.001	. 026	.001	0	0			
*U-2	0	.063	.187	.137	.053			
U-2-A	a	0	.014	. 001	0			
U-2-8	0	0	. 002	.005	.001			
U-2-C	0	0	.030	. 070	0			
U - 3	.005	.001	0	0	0			
U-4	0	.054	.001	.006	.001			
U-4-A	.011	0	.010	0	.008			
U-4-B	0	.002	0	0	0			
*U-5	0	.048	-043	0	.067			
U-5-A	0	.001	0	0	0			
U-5-B	.014	.008	.014	0	.002			
u -6	.007	.008	.002	.001	.001			

^{*} Adjusted for Natura! Flow

MOUNTAIN VIEW, LEAVITT, AETNA AND UNITED IRRIGATION DISTRICTS

NOTE

MAP COURTESY OF ALBERTA AGRICULTURE IRRIGATION DIVISION, LETHBRIDGE, ALTA.

